
## NSN 5306-00-245-7732

Machine Bolt - Page 1 of 2

**Thread Class:** 





## 3a **Thread Direction: Right-hand Thread Length:** Between 1.260 inches and 1.280 inches Fastener Length: Between 1.750 inches and 1.770 inches **Head Style:** Hexagon **Head Height:** Between 1.490 inches and 1.510 inches Width Between Flats: 0.938 inches Hole Diameter: 0.078 inches **Thread Diameter:** 0.625 inches Grip Length: Between 0.390 inches and 0.410 inches **Hole Quantity:** 3 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 180000 pounds per square inch Hole Configuration Style: Hexagon corners **Special Features:** With hole on longitudinal axis of head Material: Steel **Material Specification:** Mil-s-5626, cond c military specification single material response Surface Treatment: Cadmium **Surface Treatment Specification:**

Ps13107, fscm 76301 mfr ref single treatment response

## NSN 5306-00-245-7732

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.

