NSN 5306-00-245-7732

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-245-7732

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.260 inches and 1.280 inches |
| Fastener Length: |
| Between 1.750 inches and 1.770 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 1.490 inches and 1.510 inches |
| Width Between Flats: |
| 0.938 inches |
| Hole Diameter: |
| 0.078 inches |
| Thread Diameter: |
| 0.625 inches |
| Grip Length: |
| Between 0.390 inches and 0.410 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon corners |
| Special Features: |
| With hole on longitudinal axis of head |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-5626, cond c military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |

Ps13107, fscm 76301 mfr ref single treatment response

NSN 5306-00-245-7732

Machine Bolt - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |
| No |
| No Fiig: |

Mil-std (military Standard):

Mil-s-5626 spec.