

View Online at <https://aerobasegroup.com/nsn/5306-00-250-9456>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.374 inches and 0.441 inches

**Fastener Length:**

Between 2.634 inches and 2.681 inches

**Head Style:**

Double hexagon

**Head Height:**

0.210 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3733 inches and 0.3742 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 2.240 inches and 2.260 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.501 inches first hole and 2.533 inches first hole

**Material:**

Steel

**Material Specification:**

M-107, standard pressed steel co mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0