NSN 5306-00-250-9687

Ribbed Shoulder Bolt - Page 1 of 2

Cadmium or zinc

Surface Treatment Specification:



View Online at https://aerobasegroup.com/nsn/5306-00-250-9687 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.080 inches and 1.110 inches **Fastener Length:** Between 2.140 inches and 2.160 inches **Head Style:** Flat chamfer **Head Diameter:** 1.000 inches **Head Height:** 0.200 inches **Shoulder Diameter:** 0.520 inches first shoulder and 5.525 inches first shoulder **Shoulder Length:** 0.780 inches first shoulder **Rib Major Diameter:** Between 0.550 inches and 0.560 inches Rib Length: 0.380 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.060 inches **Rib Minor Diameter:** Between 0.530 inches and 0.540 inches **Rib Quantity:** 35 **Thread Diameter:** 0.437 inches Thready Qty Per Inch (tpi): **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** Qq-s-624 federal specification single material response **Surface Treatment:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response

NSN 5306-00-250-9687

Ribbed Shoulder Bolt - Page 2 of 2



Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0