NSN 5306-00-253-5517

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-253-5517 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.012 inches and 1.072 inches **Fastener Length:** Between 2.215 inches and 2.245 inches **Head Style:** Hexagon **Head Height:** Between 0.328 inches and 0.360 inches Width Between Flats: Between 0.928 inches and 0.939 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 1.173 inches and 1.203 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 80205-nas1010 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5306-00-253-5517

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.