NSN 5306-00-255-4242

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-255-4242

View Online at https://aerobasegroup.com/nsn/5306-00-255-4242
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.984 inches and 1.034 inches
Fastener Length:
Between 4.056 inches and 4.086 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.701 inches and 0.721 inches
Width Between Flats:
Between 0.803 inches and 0.814 inches
Extended Washer Diameter:
Between 1.220 inches and 1.230 inches
Extended Washer Thickness:
Between 0.168 inches and 0.188 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 3.052 inches and 3.072 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-00-255-4242

Shear Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0