## NSN 5306-00-257-7399

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-257-7399 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 1.717 inches **Head Diameter:** 0.750 inches **Head Height:** 0.125 inches **Distance From Centerline To Flat:** Between 0.275 inches and 0.285 inches **Shank Unthreaded Hole Diameter:** 0.109 inches first hole **Concentric Hole Diameter:** 0.194 inches **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.592 inches first hole Material: Steel **Material Specification:** Mil-s-6758 cond d4 military specification single material response **Surface Treatment:** Chromium **Surface Treatment Specification:** Qq-c-320 cl 2 federal specification single treatment response **Style Designator:** Concentric hole unthreaded **Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-00-257-7399

Internally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.