NSN 5306-00-259-1054

Machine Bolt - Page 1 of 2

Between 0.750 inches and 0.810 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

0.938 inches

За



View Online at https://aerobasegroup.com/nsn/5306-00-259-1054

Head Style:
Hexagon
Head Height:
Between 0.167 inches and 0.183 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
0.065 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.128 inches and 0.188 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Hexagon flats Surface Finish:
Surface Finish:
Surface Finish: 32.0 microinches threads
Surface Finish: 32.0 microinches threads Material:
Surface Finish: 32.0 microinches threads Material: Steel comp 8740
Surface Finish: 32.0 microinches threads Material: Steel comp 8740 Material Specification:
Surface Finish: 32.0 microinches threads Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response
Surface Finish: 32.0 microinches threads Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment:

NSN 5306-00-259-1054

Machine Bolt - Page 2 of 2



Surface Treatment S	Specification:
---------------------	----------------

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0