NSN 5306-00-259-1056

Machine Bolt - Page 1 of 2

Between 0.750 inches and 0.810 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

1.375 inches **Head Style:**

За



View Online at https://aerobasegroup.com/nsn/5306-00-259-1056

| Hexagon |
|---|
| Head Height: |
| Between 0.167 inches and 0.183 inches |
| Width Between Flats: |
| Between 0.430 inches and 0.439 inches |
| Hole Diameter: |
| 0.065 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.440 inches and 0.500 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Hole Configuration Style: |
| Hexagon flats |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams 6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| |
| |
| |

NSN 5306-00-259-1056

Machine Bolt - Page 2 of 2



| Surface Treatment S | Specification: |
|---------------------|----------------|
|---------------------|----------------|

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0