NSN 5306-00-260-7549

Square Neck Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-260-7549

| view Online at https://aerobasegroup.com/nsn/5506-00-260-7549 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.250 inches |
| Fastener Length: |
| 2.750 inches |
| Head Style: |
| Button |
| Head Diameter: |
| Between 1.032 inches and 1.094 inches |
| Head Height: |
| Between 0.250 inches and 0.270 inches |
| Neck Length: |
| Between 0.250 inches and 0.281 inches |
| Thread Diameter: |
| 0.500 inches |
| Thready Qty Per Inch (tpi): |
| 13 |
| Min. Tensile Strength (psi): |
| 55000 pounds per square inch |
| Hardness Rating: |
| 207.0 brinell standard |
| Neck Width: |
| Between 0.492 inches and 0.515 inches |
| Special Features: |
| Furnished with one square nut in accordance with federal specification ff-n-836 type1 style1 zinc coated |
| Material: |
| Steel |
| Surface Treatment: |
| Zinc |
| Surface Treatment Specification: |
| Qq-z-325, type 2, cl 3 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Specification Or Standard: |
| 1 type and 1 class and a style |
| Departure From Cited Document: |
| As modified by addition of square nut |
| Shelf Life: |

N/a

NSN 5306-00-260-7549

Square Neck Bolt - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A003b0