

View Online at <https://aerobasegroup.com/nsn/5306-00-260-7579>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.453 inches and 0.500 inches

Eye Inside Diameter:

Between 0.190 inches and 0.192 inches

Shoulder Thickness:

0.078 inches

Shank Length:

Between 0.766 inches and 0.812 inches

Eye Stock Thickness:

Between 0.120 inches and 0.130 inches

Shoulder Diameter:

0.500 inches

Shank Unthreaded Hole Diameter:

0.066 inches first hole and 0.086 inches first hole

Overall Length:

1.531 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Center Of Eye To Shank End:

1.249 inches

Distance From Threaded End To Shank Hole Center:

0.609 inches first hole and 0.641 inches first hole

Eye Outside Width:

0.500 inches

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0