

View Online at <https://aerobasegroup.com/nsn/5306-00-262-0108>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.428 inches and 0.483 inches

**Fastener Length:**

Between 1.265 inches and 1.305 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.172 inches and 0.204 inches

**Width Between Flats:**

Between 0.490 inches and 0.502 inches

**Shoulder Diameter:**

0.309 inches first shoulder and 0.312 inches first shoulder

**Shoulder Length:**

0.822 inches first shoulder and 0.837 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.077 inches first hole and 1.137 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Iron alloy 660

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0