

View Online at <https://aerobasegroup.com/nsn/5306-00-262-9632>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.062 inches

Fastener Length:

2.125 inches

Head Style:

Flat chamfer

Head Diameter:

1.187 inches

Head Height:

Between 0.307 inches and 0.317 inches

Shoulder Diameter:

0.835 inches first shoulder and 0.845 inches first shoulder

Shoulder Length:

0.833 inches first shoulder and 0.843 inches first shoulder

Rib Major Diameter:

Between 0.865 inches and 0.875 inches

Rib Length:

0.781 inches

Distance From Largest Diameter Of Bearing Surface Of Head To Ribs:

Between 0.046 inches and 0.078 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

41.0 rockwell c and 44.0 rockwell c

Minimum Yield Strength:

75000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel comp 1010

Material Specification:

Mil-s-11310 military specification single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-11310 spec.