NSN 5306-00-262-9633

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-262-9633 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.062 inches **Fastener Length:** 2.125 inches **Head Style:** Flat chamfer **Head Diameter:** 1.188 inches **Head Height:** Between 0.307 inches and 0.317 inches **Shoulder Diameter:** 0.835 inches first shoulder and 0.840 inches first shoulder **Shoulder Length:** 0.834 inches first shoulder and 0.844 inches first shoulder **Rib Major Diameter:** Between 0.865 inches and 0.875 inches Rib Length: 0.781 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: Between 0.046 inches and 0.078 inches **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): 16 **Hardness Rating:** 41.0 rockwell c and 44.0 rockwell c Minimum Yield Strength: 75000 pounds per square inch **Shoulder Shape:** Ribbed first shoulder Material: Steel comp 1025 **Material Specification:** Qq-s-634 federal specification single material response **Thread Series Designator:** Unf

Shelf Life: N/a

NSN 5306-00-262-9633

Ribbed Shoulder Bolt - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0