NSN 5306-00-265-0843

Square Neck Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-265-0843

| g |
|----------------------------------------------------------------------------------------------------------|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.750 inches |
| Fastener Length: |
| 2.000 inches |
| Head Style: |
| Button |
| Head Diameter: |
| Between 0.563 inches and 0.594 inches |
| Head Height: |
| Between 0.125 inches and 0.145 inches |
| Neck Length: |
| Between 0.125 inches and 0.156 inches |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 55000 pounds per square inch |
| Hardness Rating: |
| 207.0 brinell standard |
| Neck Width: |
| Between 0.245 inches and 0.260 inches |
| Special Features: |
| Furnished with one square nut in accordance with federal specification ff-n-836 type1 style1 zinc coated |
| Material: |
| Steel |
| Surface Treatment: |
| Zinc |
| Surface Treatment Specification: |
| Qq-z-325, type 2, cl 3 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Specification Or Standard: |
| 1 type and 1 class and a style |
| Departure From Cited Document: |
| As modified by addition of square nut |
| Shelf Life: |
| |

N/a

NSN 5306-00-265-0843

Square Neck Bolt - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

A003b0