

View Online at <https://aerobasegroup.com/nsn/5306-00-268-1543>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.531 inches

Eye Inside Diameter:

Between 0.250 inches and 0.253 inches

Shoulder Thickness:

0.094 inches

Shank Length:

6.109 inches

Eye Stock Thickness:

Between 0.183 inches and 0.193 inches

Shoulder Diameter:

0.6250 inches

Shank Unthreaded Hole Diameter:

0.066 inches first hole and 0.086 inches first hole

Overall Length:

7.000 inches

Thread Diameter:

0.312 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Center Of Eye To Shank End:

Between 6.778 inches and 6.784 inches

Distance From Threaded End To Shank Hole Center:

5.922 inches first hole

Eye Outside Width:

0.625 inches

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 3 federal specification single treatment response

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0