
## NSN 5306-00-269-6864

Machine Bolt - Page 1 of 2





Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.687 inches and 0.747 inches

#### Fastener Length:

1.562 inches

Head Style:

Hexagon

Head Height:

Between 0.178 inches and 0.198 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

## Thread Diameter:

0.312 inches

Grip Length:

Between 0.815 inches and 0.875 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

125000 pounds per square inch

## Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

#### Surface Finish:

63.0 microinches grip

## Material:

Steel comp 8740

## Material Specification:

Ams 6322 assn standard single material response

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Ams 2400 assn standard single treatment response

## **Thread Series Designator:**

Unf

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-00-269-6864

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

