## NSN 5306-00-269-6975

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-269-6975

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.687 inches and 0.747 inches   |
| Fastener Length:  |
| 0.812 inches  |
| Head Style:   |
| Hexagon   |
| Head Height:  |
| Between 0.178 inches and 0.198 inches   |
| Width Between Flats:  |
| Between 0.492 inches and 0.502 inches   |
| Thread Diameter:  |
| 0.312 inches  |
| Grip Length:  |
| Between 0.065 inches and 0.125 inches   |
| Features Provided:  |
| Finished head   |
| Thready Qty Per Inch (tpi):   |
| 24  |
| Min. Tensile Strength (psi):  |
| 125000 pounds per square inch   |
| Hardness Rating:  |
| naraness rating.  |
| 26.0 rockwell c and 32.0 rockwell c   |
| •   |
| 26.0 rockwell c and 32.0 rockwell c   |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish:  |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish:  63.0 microinches grip   |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material:   |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740   |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740  Material Specification:  |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment:  |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment: Cadmium  |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment: Cadmium  Surface Treatment Specification:  |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment: Cadmium  Surface Treatment Specification: Ams 2400 assn standard single treatment response   |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment: Cadmium  Surface Treatment Specification: Ams 2400 assn standard single treatment response  Thread Series Designator:                  |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment: Cadmium  Surface Treatment Specification: Ams 2400 assn standard single treatment response  Thread Series Designator: Unf              |
| 26.0 rockwell c and 32.0 rockwell c  Surface Finish: 63.0 microinches grip  Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment: Cadmium  Surface Treatment Specification: Ams 2400 assn standard single treatment response  Thread Series Designator: Unf  Shelf Life: |

## NSN 5306-00-269-6975

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0