

View Online at <https://aerobasegroup.com/nsn/5306-00-270-2874>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.553 inches and 0.633 inches

**Fastener Length:**

Between 1.178 inches and 1.198 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.115 inches and 0.135 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Shank Unthreaded Hole Diameter:**

0.065 inches and 0.072 inches first hole

**End Application:**

Spec item

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.565 inches and 0.625 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.068 inches and 1.088 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0