

View Online at <https://aerobasegroup.com/nsn/5306-00-271-4797>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.641 inches

**Eye Inside Diameter:**

Between 0.375 inches and 0.378 inches

**Shoulder Thickness:**

0.094 inches

**Shank Length:**

Between 2.681 inches and 2.734 inches

**Eye Stock Thickness:**

0.188 inches

**Shoulder Diameter:**

0.750 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Overall Length:**

3.719 inches

**Thread Diameter:**

0.375 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Threaded End To Shank Hole Center:**

2.500 inches first hole

**Eye Outside Width:**

0.750 inches

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Style Designator:**

Round, closed w/shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0