

Thread Direction: Right-hand Thread Length: 0.875 inches Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Sheff Life:	2a Thread Direction: Right-hand Thread Length: 0.875 inches Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	View Or	line at https://aerobasegroup.com/nsn/5306-00-272-4233
Right-hand Right-hand Thread Length: 0.875 inches Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Thread Direction: Right-hand Thread Length: 0.875 inches Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.78 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cenell 3.625 inches first hole Material: Steel comp 1035 Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread	Class:
Right-hand Right-hand Thread Length: 0.875 inches Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Right-hand Right-hand Thread Length: 0.875 inches Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 24.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Sheff Life: N/a Unit Of Measure: Demilitarization:	2a	
Thread Length: 0.875 inches Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.234 inches Width Between Flats: 0.234 inches Shank Unthreaded Hole Diameter: 0.3012 inches Shank Unthreaded Hole Diameter: 0.312 inches Features Provided: Finished head Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Thread Length: 0.875 inches Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread	Direction:
0.875 inches Fastener Length: 3.750 inches Head Style: Head Style: Head Height: 0.234 inches Width Between Flats: 0.234 inches Width Between Flats: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	0.875 inches Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.304 inches Shank Unthreaded Hole Diameter: 0.305 inches Shank Unthreaded Hole Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: - Demilitarization:	Right-ha	Ind
Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Fastener Length: 3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread	Length:
3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.234 inches Width Between Flats: 0.234 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	3.750 inches Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	0.875 in	ches
Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.372 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Head Style: Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Fastene	er Length:
Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.508 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Hexagon Hexagon Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.3012 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	3.750 in	ches
Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Head Height: 0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Head S	yle:
0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	0.234 inches Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Hexago	n
Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Centor 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Width Between Flats: 0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Head H	eight:
0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	0.500 inches Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	0.234 in	ches
Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Shank Unthreaded Hole Diameter: 0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Width E	etween Flats:
0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	0.078 inches first hole Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: 	0.500 in	ches
Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Thread Diameter: 0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Shank I	Jnthreaded Hole Diameter:
0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	0.312 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	0.078 in	ches first hole
Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Features Provided: Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread	Diameter:
Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	0.312 in	ches
Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Thready Qty Per Inch (tpi): 24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Feature	s Provided:
24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	24 Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Finished	l head
Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Hardness Rating: 248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread	/ Qty Per Inch (tpi):
248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	248.0 brinell standard and 285.0 brinell standard Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	24	
Distance From Head Largest Bearing Surface To Shank Hole Cent 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Distance From Head Largest Bearing Surface To Shank Hole Cen 3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Hardne	ss Rating:
3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	3.625 inches first hole Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	248.0 bi	inell standard and 285.0 brinell standard
Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Material: Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Distanc	e From Head Largest Bearing Surface To Shank Hole Cent
Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Steel comp 1035 Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	3.625 in	ches first hole
Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Material Specification: Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Materia	l:
Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a	Sae assn standard single material response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Steel co	mp 1035
Thread Series Designator: Unf Shelf Life: N/a	Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Materia	Specification:
Unf Shelf Life: N/a	Unf Shelf Life: N/a Unit Of Measure: Demilitarization:	Sae ass	n standard single material response
Shelf Life: N/a	Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread	Series Designator:
N/a	N/a Unit Of Measure: Demilitarization:	Unf	
	Unit Of Measure: Demilitarization:	Shelf Li	fe:
Unit Of Measure:	 Demilitarization:	N/a	
	Demilitarization:	Unit Of	Measure:
	INU	No	
	E III I	Fiig:	

A003b0