## NSN 5306-00-272-5142

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-272-5142

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.625 inches
Fastener Length:
1.875 inches
Head Style:
Hexagon
Head Height:
0.375 inches
Width Between Flats:
0.750 inches
Shank Unthreaded Hole Diameter:
0.109 inches first hole
Thread Diameter:
0.500 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
40
13
Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 69000 pounds per square inch
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b Distance From Head Largest Bearing Surface To Shank Hole Center:
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole Product Name:
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole Product Name: Navy special project
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole Product Name: Navy special project Material:
Min. Tensile Strength (psi): 69000 pounds per square inch  Hardness Rating: 100.0 rockwell b  Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole  Product Name: Navy special project  Material: Steel comp 3135
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole Product Name: Navy special project Material: Steel comp 3135 Material Specification:
Min. Tensile Strength (psi): 69000 pounds per square inch  Hardness Rating: 100.0 rockwell b  Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole  Product Name: Navy special project  Material: Steel comp 3135  Material Specification: Sae assn standard single material response
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b  Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole  Product Name: Navy special project  Material: Steel comp 3135  Material Specification: Sae assn standard single material response Surface Treatment:
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole Product Name: Navy special project Material: Steel comp 3135 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole Product Name: Navy special project Material: Steel comp 3135 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Thread Series Designator:
Min. Tensile Strength (psi): 69000 pounds per square inch Hardness Rating: 100.0 rockwell b Distance From Head Largest Bearing Surface To Shank Hole Center: 1.719 inches first hole Product Name: Navy special project Material: Steel comp 3135 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Thread Series Designator: Unc

As modified by material, head h, thd cl and cotter pin hole

## NSN 5306-00-272-5142

Machine Bolt - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0