## NSN 5306-00-273-2546

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-273-2546 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.358 inches and 0.403 inches **Fastener Length:** Between 4.451 inches and 4.466 inches **Head Style:** Round w/wrench flats **Head Diameter:** 0.766 inches **Head Height:** Between 0.065 inches and 0.080 inches Width Between Flats: 0.688 inches **Shank Unthreaded Hole Diameter:** 0.076 inches and 0.086 inches first hole **Concentric Hole Depth:** Between 3.670 inches and 3.685 inches **Concentric Hole Diameter:** Between 0.483 inches and 0.490 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 135000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 4.312 inches first hole **Product Name:** Navy special project Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Style Designator:** Concentric hole unthreaded **Thread Series Designator:** 

Unf
Shelf Life:

N/a

## NSN 5306-00-273-2546

Internally Relieved Body Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0