NSN 5306-00-273-4417

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-273-4417

| · |
|------------------------------------------------------------------|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.291 inches and 0.341 inches |
| Fastener Length: |
| Between 2.301 inches and 2.331 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.125 inches and 0.140 inches |
| Width Between Flats: |
| Between 0.430 inches and 0.439 inches |
| Hole Diameter: |
| 0.046 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Shank Unthreaded Hole Diameter: |
| 0.076 inches first hole and 0.086 inches first hole |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 1.990 inches and 2.010 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon corners |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 2.173 inches first hole and 2.223 inches first hole |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response |
| Thread Series Designator: |

Unf

NSN 5306-00-273-4417

Shear Bolt - Page 2 of 2



| | | ife: | |
|--|--|------|--|
| | | | |
| | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0