NSN 5306-00-273-4417

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-273-4417

·
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.291 inches and 0.341 inches
Fastener Length:
Between 2.301 inches and 2.331 inches
Head Style:
Hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
0.046 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Thread Diameter:
0.250 inches
Grip Length:
Between 1.990 inches and 2.010 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Distance From Head Largest Bearing Surface To Shank Hole Center:
2.173 inches first hole and 2.223 inches first hole
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response
Thread Series Designator:

Unf

NSN 5306-00-273-4417

Shear Bolt - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0