NSN 5306-00-274-2723



Ribbed Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-274-2723 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.750 inches and 0.766 inches **Fastener Length:** Between 1.344 inches and 1.360 inches **Head Style:** Flat chamfer **Head Diameter:** 0.875 inches **Head Height:** 0.156 inches **Shoulder Diameter:** 0.594 inches first shoulder **Shoulder Length:** 0.412 inches first shoulder **Rib Major Diameter:** 0.625 inches Rib Length: 0.412 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.062 inches **Thread Diameter:** 0.500 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 110000 pounds per square inch **Hardness Rating:** 24.0 rockwell c **Shoulder Shape:** Ribbed first shoulder

Ribbed first shoulder

Material:
Steel comp 1020

Material Specification:
Qq-s-634 federal specification single material response

Thread Series Designator:
Unf

NSN 5306-00-274-2723

Ribbed Shoulder Bolt - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0