NSN 5306-00-275-4512

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-275-4512

Ba Thread Direction: Right-hand Thread Length: 0.260 inches Fastener Length: Between 1.296 inches and 1.328 inches Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.262 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: D.164 inches With Across Flats: Between 0.140 inches and 0.142 inches Thready Chy Per Inch (tpi): 32 Material Specification Stalless steel Material Specification Stalless steel Material Specification single material response Starface Treatment: Davide film Starface Treatment Specification: Estaagouo, fiscm	Thread Class:	
Thread Direction: Right-hand Thread Length: 0.250 inches Fastenr Length: Date of inches and 1.328 inches Head Style: Flat chamfer Head Director: Between 0.262 inches and 0.270 inches Head Height: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.164 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.126 inches and 1.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Difter Diameter: D.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thread Quy Per Inch (tpi): 32 Material: Stainless steel Material Specification: Chread Specification: Pas-763 federal specification single material response Surface Treatment: Dried Specification: FiseDagond, isom 9742 mfr ref single treatment response Surface Treatment: Dried Sheft Life: Via Material:		
Right-hand Thread Length: 0.250 inches Fastener Length: Between 1.296 inches and 1.328 inches Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.170 inches Head Height: Between 0.159 inches and 0.126 inches First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches With Across Flats: Between 0.1040 inches and 0.142 inches Thread Jameter: 0.164 inches With Across Flats: Between 0.140 inches and 0.142 inches Thread Jameter: 0.164 inches With Across Flats: Between 0.140 inches and 0.142 inches Thread Jameter: 0.164 inches With Across Flats: Between 0.140 inches and 0.142 inches Thread Specification: Days-763 federal specification single material response Surface Treatment: Days-763 federal specification: Systeace Treatment: Daysdaught, fscm 37942 mfr ref single treatment response Thread Series Designator: Hexagon Sheft Life: Via Unc		
Thread Length: D.250 inches Fastener Length: Between 1.296 inches and 1.328 inches Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.176 inches First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: D.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpl): 32 Material: Stainless steel Material Specification: Day-afol fedral specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fa80ag00, fscm 97942 mfr ref single treatment response Furead Series Designator: Unc Sheff Life: Va		
2.250 inches Fastener Length: Between 1.296 inches and 1.328 inches Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.262 inches and 0.270 inches Head Height: Between 0.169 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.164 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.464 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: D.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Oty Per Inch (tpi): 32 Material Stainless steel Material Specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fised Sourge Treatment Fised Sourge Treatment response First Sourge Treatment Specification: Fised Sourge Treatment Fi		
Fastener Length: Between 1.296 inches and 1.328 inches Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.164 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.46 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Waterial Stainless steel Material Specification: Cays-763 federal specification single material response Surface Treatment: Oxide film Starlesc Treatment Specification: Fised Sougo0, facen 97942 mfr ref single treatment response Thread Stries Designator: Jinc Sheft Life: Wa Unc Sheft Life: Wa Unc Sheft Life: Wa		
Between 1.296 inches and 1.328 inches Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.270 inches First Diameter From Head: Between 0.159 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.164 inches First Diameter From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: D.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Cty Per Inch (tpi): 32 Waterial: Stainless steel Material Specification: Ques-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: Va Unc		
Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thread Var Per Inch (tpi): 32 Material: Stainless steel Material Specification: 2q-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: Via	-	
Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response: Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: Via Unc Shelf Life: Via		
Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thread Vy Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qa-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: Wa		
Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Uy Per Inch (tpi): 32 Material: Stainless steel Material Specification single material response Surface Treatment Specification: Es80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: Na		
Head Height: Between 0.159 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Dy Per Inch (tpi): 32 Material: Stainless steel Material Specification Surface Treatment: Dxide film Surface Treatment Specification: Es80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Dxide film Surface Treatment Specification: Shelf Life: N/a		
Between 0.159 inches and 0.164 inches First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thread Vap Per Inch (tpi): 32 Material: Stainless steel Material Specification: Cq-s-763 federal specification single material response Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Sthef Life: Va		
First Diameter From Head: Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: Via	-	
Between 0.121 inches and 0.126 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Between 0.159 inches and 0.164 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.046 inches and 1.078 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a	First Diameter From Head:	
Between 1.046 inches and 1.078 inches internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a	Between 0.121 inches and 0.126 inches	
Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
Hexagon Thread Diameter: D.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: F-s80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: Na	Between 1.046 inches and 1.078 inches	
Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: Va	Internal Drive Style:	
20.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: V/a Unit Of Measure:	Hexagon	
Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Dxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a	Thread Diameter:	
Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	0.164 inches	
Thready Qty Per Inch (tpi): 32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Width Across Flats:	
32 Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Between 0.140 inches and 0.142 inches	
Material: Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Thready Qty Per Inch (tpi):	
Stainless steel Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	32	
Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Material:	
Qq-s-763 federal specification single material response Surface Treatment: Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Stainless steel	
Surface Treatment: Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Material Specification:	
Oxide film Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Qq-s-763 federal specification single material response	
Surface Treatment Specification: Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Surface Treatment:	
Fs80ag00, fscm 97942 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Oxide film	
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Surface Treatment Specification:	
Unc Shelf Life: N/a Unit Of Measure:	Fs80ag00, fscm 97942 mfr ref single treatment response	
Shelf Life: N/a Unit Of Measure:	Thread Series Designator:	
N/a Unit Of Measure:	Unc	
Unit Of Measure:	Shelf Life:	
	N/a	
-	Unit Of Measure:	
Demilitarization:	Demilitarization:	
Νο	No	

NSN 5306-00-275-4512

Internal Wrenching Bolt - Page 2 of 2

Fiig: A003b0

