NSN 5306-00-275-5700

Ribbed Shoulder Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-275-5700

| | read Class: |
|-----|--|
| 3a | |
| Th | read Direction: |
| Ri | ght-hand |
| Th | read Length: |
| 0.6 | 25 inches |
| Fa | stener Length: |
| 1.1 | 88 inches |
| He | ad Style: |
| He | xagon |
| He | ad Height: |
| 0.1 | 88 inches |
| Wi | dth Between Flats: |
| 0.5 | 562 inches |
| Sh | oulder Diameter: |
| 0.3 | 390 inches first shoulder and 0.400 inches first shoulder |
| Sh | oulder Length: |
| 0.4 | 106 inches first shoulder |
| Ril | o Major Diameter: |
| Be | tween 0.415 inches and 0.423 inches |
| Ril | b Length: |
| 0.1 | 56 inches |
| Di | stance From Largest Diameter Of Bearing Surface Of Head To Ribs: |
| 0.0 | 062 inches |
| Th | read Diameter: |
| 0.3 | 375 inches |
| Th | ready Qty Per Inch (tpi): |
| 24 | |
| Sh | oulder Shape: |
| Rił | bbed first shoulder |
| Ма | iterial: |
| Ste | eel |
| Th | read Series Designator: |
| Un | f |
| Sh | elf Life: |
| N/a | a |
| Un | it Of Measure: |
| | |
| De | militarization: |
| No | |
| | |