NSN 5306-00-275-8503

Internal Wrenching Bolt - Page 1 of 2

Unf



material

View Online at https://aerobasegroup.com/nsn/5306-00-275-8503

| Thread CI | ass: |
|---------------|---|
| 3a | |
| Thread Di | rection: |
| Right-hand | t de la construcción de |
| Thread Le | ength: |
| | .475 inches and 0.525 inches |
| Fastener | Length: |
| Between 1 | .735 inches and 1.765 inches |
| Head Diar | neter: |
| Between 0 | 0.428 inches and 0.438 inches |
| Head Heig | yht: |
| 0.250 inch | es |
| Hole Dian | neter: |
| 0.037 inch | es |
| Internal D | rive Style: |
| Hexagon | |
| Thread Di | ameter: |
| 0.250 inch | es |
| Width Acr | ross Flats: |
| Between C | 0.188 inches and 0.190 inches |
| Hole Qua | ntity: |
| 4 | |
| Hole Type | |
| Drilled | |
| Thready Q | Qty Per Inch (tpi): |
| 28 | |
| Min. Tens | ile Strength (psi): |
| 160000 pc | ounds per square inch |
| Hardness | Rating: |
| 34.0 rockw | vell c and 40.0 rockwell c |
| Hole Conf | iguration Style: |
| Round Ion | gitudinal hole |
| Material: | |
| Steel com | p 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 |
| Material S | pecification: |
| Mil-s-5626 | military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military |
| specification | on 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th mat |
| response | |
| Surface T | reatment: |
| Cadmium | and chromate |
| Surface T | reatment Specification: |
| Qq-p-416, | type 2 cl 2 federal specification single treatment response |
| Thread Se | eries Designator: |
| | |

NSN 5306-00-275-8503

Internal Wrenching Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.

