Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-276-5522

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Fastener Length:	
1.678 inches	
Head Style:	
Hexagon	
Head Height:	
Between 0.126 incl	nes and 0.141 inches
Width Between Fl	ats:
Between 0.430 incl	nes and 0.439 inches
Shank Unthreade	d Hole Diameter:
0.076 inches first l	nole and 0.086 inches first hole
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 1.250 incl	nes and 1.266 inches
Features Provided	1:
Finished head	
Thready Qty Per I	nch (tpi):
28	
Hardness Rating:	
39.0 rockwell c ar	d 45.0 rockwell c
Special Features:	
Balls in shank	
Material:	
Steel comp 8740 o	or steel comp e4340 or steel comp 4340
Material Specifica	tion:
Mil-s-6049 military	specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5000 militar
specification 3rd m	aterial response
Surface Treatmen	t:
Cadmium and chro	omate
Surface Treatmen	t Specification:
Qq-p-416, type 2, c	lass 3 federal specification all treatment responses
Thread Series Des	signator:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	

NSN 5306-00-276-5522

Machine Bolt - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-s-6049 spec.

