

View Online at <https://aerobasegroup.com/nsn/5306-00-280-3333>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.589 inches and 0.639 inches

Fastener Length:

Between 1.474 inches and 1.504 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.251 inches first hole and 1.291 inches first hole

Material:

Stainless steel

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0