

View Online at <https://aerobasegroup.com/nsn/5306-00-281-2858>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.317 inches and 0.346 inches

**Fastener Length:**

1.670 inches

**Head Style:**

Hexagon

**Head Height:**

0.120 inches

**Width Between Flats:**

Between 0.744 inches and 0.750 inches

**Shoulder Diameter:**

0.4985 inches first shoulder and 0.4993 inches first shoulder

**Shoulder Length:**

1.270 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.075 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Criticality Code Justification:**

Aatn

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.560 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Material Specification:**

Mil-s-5626 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Lc+77-1061, class 3, type 2, fscm 36659 mfr ref single treatment response

**Test Data Document:**

36659-lc+72-1076 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.