

View Online at <https://aerobasegroup.com/nsn/5306-00-281-2865>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.457 inches and 0.476 inches

Fastener Length:

1.940 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.125 inches

Head Height:

0.120 inches

Width Between Flats:

0.875 inches

Shoulder Diameter:

0.498 inches first shoulder and 0.499 inches first shoulder

Shoulder Length:

1.400 inches first shoulder and 1.410 inches first shoulder

Shank Unthreaded Hole Diameter:

0.105 inches all holes and 0.110 inches all holes

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.850 inches second hole and 1.860 inches second hole

Shoulder Shape:

Round first shoulder

Special Features:

2 drilled holes in shank 90 degrees apart

Material:

Steel

Material Specification:

Mil-s-5000, cond e4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Lc+77-1061, type 2, cl 2, fscm 36659 mfr ref single treatment response

Test Data Document:

36659-lc+72-1076 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.