

View Online at <https://aerobasegroup.com/nsn/5306-00-281-5210>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.859 inches and 0.891 inches

Fastener Length:

Between 0.984 inches and 1.016 inches

Head Style:

Hexagon

Head Height:

Between 0.218 inches and 0.250 inches

Width Between Flats:

Between 0.546 inches and 0.578 inches

Shank Unthreaded Hole Diameter:

0.875 inches first hole

Thread Diameter:

0.375 inches

Features Provided:

Unfinished head

Thready Qty Per Inch (tpi):

24

Hardness Rating:

15.2 rockwell c and 25.4 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.093 inches first hole and 0.125 inches first hole

Material:

Steel comp 1030 or steel comp 1037 or steel comp 1038 or steel comp 1035 or steel comp 1040

Material Specification:

Qq-s-631 fs1030 federal specification 1st material response or qq0s0631 fs1037 federal specification 2nd material response or qq-s-631 fs1038 federal specification 3rd material response or qq-s-634 fs1035 federal specification 4th material response or qq-s-634 fs1040 federal specification 5th material response

Surface Treatment:

Cadmium or zinc

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0