

View Online at <https://aerobasegroup.com/nsn/5306-00-281-5210>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.859 inches and 0.891 inches

**Fastener Length:**

Between 0.984 inches and 1.016 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.218 inches and 0.250 inches

**Width Between Flats:**

Between 0.546 inches and 0.578 inches

**Shank Unthreaded Hole Diameter:**

0.875 inches first hole

**Thread Diameter:**

0.375 inches

**Features Provided:**

Unfinished head

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

15.2 rockwell c and 25.4 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.093 inches first hole and 0.125 inches first hole

**Material:**

Steel comp 1030 or steel comp 1037 or steel comp 1038 or steel comp 1035 or steel comp 1040

**Material Specification:**

Qq-s-631 fs1030 federal specification 1st material response or qq0s0631 fs1037 federal specification 2nd material response or qq-s-631 fs1038 federal specification 3rd material response or qq-s-634 fs1035 federal specification 4th material response or qq-s-634 fs1040 federal specification 5th material response

**Surface Treatment:**

Cadmium or zinc

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0