

View Online at <https://aerobasegroup.com/nsn/5306-00-281-7011>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.486 inches and 0.536 inches

**Fastener Length:**

Between 2.558 inches and 2.588 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.281 inches and 0.296 inches

**Width Between Flats:**

Between 0.865 inches and 0.877 inches

**Grip Diameter:**

Between 0.5610 inches and 0.5615 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 2.052 inches and 2.072 inches

**Thready Qty Per Inch (tpi):**

18

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.422 inches first hole and 2.474 inches first hole

**Material:**

Titanium alloy

**Material Specification:**

Nas 4928, alloy 6al-4v assn standard single material response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas1261 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0