## NSN 5306-00-281-7172

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-281-7172



Thread Class:

3a

**Thread Direction:** 

Right-hand

Thread Length:

Between 0.516 inches and 0.586 inches

Fastener Length:

Between 1.838 inches and 1.888 inches

**Head Style:** 

Double hexagon w/hole

Head Height:

Between 0.338 inches and 0.358 inches

#### Width Between Flats:

Between 0.367 inches and 0.376 inches

#### **Extended Washer Diameter:**

Between 0.521 inches and 0.531 inches

#### **Extended Washer Thickness:**

Between 0.072 inches and 0.092 inches

#### **Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

#### Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

Thread Diameter:

0.312 inches

Grip Length:

Between 1.302 inches and 1.322 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

### Distance From Head Largest Bearing Surface To Shank Hole Center:

1.630 inches first hole and 1.690 inches first hole

Material:

- Stainless steel
- Surface Treatment:

Passivate

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

# NSN 5306-00-281-7172

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

