NSN 5306-00-281-7468

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-281-7468 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.516 inches and 0.586 inches **Fastener Length:** Between 2.838 inches and 2.888 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.338 inches and 0.358 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.072 inches and 0.092 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.081 inches first hole **End Application:** Aircraft, eagle f-15 **Thread Diameter:** 0.312 inches **Grip Length:** Between 2.302 inches and 2.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.630 inches first hole and 2.690 inches first hole Material: Stainless steel **Surface Treatment: Passivate**

Thread Series Designator: Unjf **Specification Data:** 76301-st3-571 manufacturers standard

NSN 5306-00-281-7468

Shear Bolt - Page 2 of 2



| She | lf I | Life | е: |
|-----|------|------|----|
| | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0