

View Online at <https://aerobasegroup.com/nsn/5306-00-281-9719>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.485 inches and 0.515 inches

**Fastener Length:**

Between 1.610 inches and 1.640 inches

**Head Style:**

Bevel-conical

**Head Diameter:**

Between 2.100 inches and 2.125 inches

**Head Height:**

1.205 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 1.251 inches and 1.256 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Steel comp 4140 or steel comp 6150 or steel comp 8740 or steel comp 3140

**Material Specification:**

Mil-s-5000 condition c, 4 military specification 1st material response or mil-s-6049 condition c, 4 military specification 2nd material response or mil-s-8503 condition c, 4 military specification 3rd material response or qq-s-690 condition e, 4 federal specification 4th material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.