## NSN 5306-00-282-0029

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-282-0029 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.688 inches **Fastener Length:** 3.125 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.615 inches and 0.625 inches **Head Height:** 0.343 inches **Hole Diameter:** 0.055 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.3755 inches and 0.3785 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Round Material: Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel **Material Specification:** Mil-s-5000, c4 military specification 1st material response or mil-s-6049, cond c4 military specification 2nd material response or mil-s-8503, cond c4 military specification 3rd material response or qq-s-690, cond e4-canceled federal specification 4th material response **Surface Treatment:** Cadmium **Thread Series Designator:** 

N/a

Unf

Shelf Life:

## NSN 5306-00-282-0029

Internal Wrenching Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.