

View Online at <https://aerobasegroup.com/nsn/5306-00-282-2168>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.5475 inches and 0.5775 inches

Fastener Length:

Between 2.0475 inches and 2.0775 inches

Head Diameter:

Between 0.523 inches and 0.531 inches

Head Height:

0.276 inches

Hole Diameter:

0.055 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.312 inches

Width Across Flats:

Between 0.313 inches and 0.315 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.891 inches first hole

Material:

Steel comp e4340 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5000, cond c4 military specification 1st material response or mil-s-6049, cond c4 military specification 2nd material response or mil-s-8503, cond c4 military specification 3rd material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.