

View Online at <https://aerobasegroup.com/nsn/5306-00-282-3308>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.548 inches and 0.578 inches

**Fastener Length:**

Between 1.2975 inches and 1.3275 inches

**Head Style:**

Bevel-conical

**Head Diameter:**

Between 0.523 inches and 0.531 inches

**Head Height:**

0.276 inches

**Hole Diameter:**

0.055 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.312 inches

**Width Across Flats:**

Between 0.313 inches and 0.315 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Round

**Material:**

Steel comp 4340 or steel comp 8740 or steel comp 6150

**Material Specification:**

Mil-s-5000, cond c4 military specification 1st material response or mil-s-6049, cond c4 military specification 2nd material response or mil-s-8503, cond c4 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.