NSN 5306-00-282-3530

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-282-3530 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.485 inches and 0.515 inches **Fastener Length:** Between 0.860 inches and 0.890 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.430 inches and 0.438 inches **Head Height:** 0.226 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.2190 inches and 0.2210 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response or an-qq-s-690 cond. E4 federal specification 4th material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf **Specification Data:** 80205-nas144 through nas158 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization:

NSN 5306-00-282-3530

Internal Wrenching Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.