

View Online at <https://aerobasegroup.com/nsn/5306-00-282-3530>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.485 inches and 0.515 inches

Fastener Length:

Between 0.860 inches and 0.890 inches

Head Style:

Bevel-conical

Head Diameter:

Between 0.430 inches and 0.438 inches

Head Height:

0.226 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

Between 0.2190 inches and 0.2210 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response or an-qq-s-690 cond. E4 federal specification 4th material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Specification Data:

80205-nas144 through nas158 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.