## NSN 5306-00-282-4009

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-282-4009 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.5475 inches and 0.5775 inches **Fastener Length:** Between 0.860 inches and 0.890 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.740 inches and 0.750 inches **Head Height:** 0.407 inches **Hole Diameter:** 0.055 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.313 inches and 0.315 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Round Material: Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel **Material Specification:** Mil-s-5000 cond c, 4 military specification 1st material response or mil-s-6049 cond c, 4 military specification 2nd material response or mil-s-8503 cond c, 4 military specification 3rd material response or an-qq-s-689 cond e, 4 federal specification 4th material response **Surface Treatment:** Cadmium

Shelf Life: N/a

Unf

**Thread Series Designator:** 

## NSN 5306-00-282-4009

Internal Wrenching Bolt - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.