

View Online at <https://aerobasegroup.com/nsn/5306-00-282-4356>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.172 inches and 1.207 inches

Fastener Length:

Between 3.360 inches and 3.390 inches

Head Style:

Bevel-conical

Head Diameter:

Between 1.424 inches and 1.438 inches

Head Height:

0.846 inches

Hole Diameter:

0.070 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.875 inches

Width Across Flats:

Between 0.7507 inches and 0.7547 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.156 inches first hole

Material:

Steel comp e4340 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5000 cond c4 military specification 1st material response or mil-s-6049 comp c4 military specification 2nd material response or mil-s-8503 cond c4 military specification 3rd material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unjf

Specification Data:

80205-nas154 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.