
## NSN 5306-00-282-4550

Internal Wrenching Bolt - Page 1 of 2





Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.6725 inches and 0.7025 inches
Fastener Length:
Between 1.673 inches and 1.703 inches
Head Style:
Bevel-conical
Head Diameter:
Between 0.615 inches and 0.625 inches
Head Height:
0.343 inches
Hole Diameter:
0.055 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.3755 inches and 0.3785 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.281 inches first hole
Material:
Steel
Surface Treatment:
Cadmium
Thread Series Designator:
Unf

## NSN 5306-00-282-4550

Internal Wrenching Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

