NSN 5306-00-282-4679



Internal Wrenching Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-282-4679 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.485 inches and 0.515 inches **Fastener Length:** Between 2.9225 inches and 2.9525 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.430 inches and 0.438 inches **Head Height:** 0.226 inches **Hole Diameter:** 0.055 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.219 inches and 0.221 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Round Material: Steel comp 4140 or steel comp 6150 or steel comp 8740 or steel comp 3140 **Material Specification:** Mil-s-5000 cond c, 4 military specification 1st material response or mil-s-6049 cond c, 4 military specification 2nd material response or mil-s-8503 cond c, 4 military specification 3rd material response or qq-s-690 cond e, 4 federal specification 4th material response **Surface Treatment:** Cadmium **Thread Series Designator:**

N/a

Unf

Shelf Life:

NSN 5306-00-282-4679

Internal Wrenching Bolt - Page 2 of 2



ι	Jnit	Of	Measure:
•	,,,,,	•	moudai c.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.