

View Online at <https://aerobasegroup.com/nsn/5306-00-282-4748>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.6725 inches and 0.7025 inches

Fastener Length:

Between 1.860 inches and 1.890 inches

Head Style:

Bevel-conical

Head Diameter:

Between 0.615 inches and 0.625 inches

Head Height:

0.343 inches

Hole Diameter:

0.700 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.375 inches

Width Across Flats:

Between 0.3755 inches and 0.3785 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Round

Material:

Steel comp e4340 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5000 cond c4 military specification 1st material response or mil-s-6049 cond c4 military specification 2nd material response or mil-s-8503 cond c4 military specification 3rd material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Specification Data:

80205-nas144 through nas158 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.