## NSN 5306-00-282-5080

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-282-5080



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

Between 0.688 inches and 0.719 inches

#### Fastener Length:

0.750 inches

#### **Head Style:**

Crowned hexagon

#### **Head Height:**

0.141 inches

#### Width Between Flats:

0.438 inches

#### **Thread Diameter:**

0.250 inches

## Grip Length:

Between 0.031 inches and 0.062 inches

#### Features Provided:

Finished head

## Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

125000 pounds per square inch

## Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

#### Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

#### Material Specification:

Mil-b-6812 military specification all material responses

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

#### **Thread Series Designator:**

Unf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5306-00-282-5080

Machine Bolt - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-b-6812 spec.

